



LUBRICANT SEALING REMOVER

A02152 - 500 ML

Unlocks and lubricates effectively.

- Anti-corrosive
- Multi-position valve
- Does not damage parts



● Application:

Removes rust and deposits of all kinds.
Without risk for metal, rubber, wood.
Non-flammable propellant gas (CO2).
Presents stripping and degreasing properties, leaving an anti-corrosion film after evaporation of the solvents.

Produced with a low pour point, it quickly penetrates corroded masses such as rust, disintegrating them, thus allowing the parts to be unblocked. treated.
Multi-position valve for easy use in hard-to-reach places

TECHNICAL DATA:

Odor: Hydrocarbon / Density: 0.81 +/-0.02

● Directions for use:

Shake the aerosol before use.
Spray directly on the parts to be unblocked.
Leave it to act for a few minutes.

● Areas of use:

- All types of doors
- Joints, bolts, gears
- Automotive, aviation and maritime sectors

● Packaging:

Packaging unit (U.C): 500mL aerosol
Tinplate case diameter: 65 mm/Height: 195mm
Sales unit: Box of 12 units
Palettization: 1080 units / 90 boxes

● Legislation:

GENERAL PUBLIC AND PROFESSIONAL USE

Dangerous. Extremely flammable aerosol. respect the precautions for use. consult the safety data sheet (msd), available on request.
Our technical data sheets have been produced based on our current knowledge; certain elements are subject to change.
Non-contractual photo. 01/01/2026 Index 3,2