TECHNICAL SHEET
Industry

PUCK®



STOP RUST
A19128 - 500ML

Clear anti-rust coating.
- Multi-position valve
- Very high covering and penetrating power
- Resists UV and oxidation
- Colorless



Application:
Colorless anti-rust coating, glossy finish.
Resin-based product which penetrates rust and thus prevents its proliferation.
Protects metal, iron, steel and sheet metal against oxidation and corrosion. Resists UV, humidity and oxidation.
Use on oxidized and very oxidized surfaces. Also usable as an undercoat of primer.
TECHNICAL DATA:
Colorless liquid appearance / Solvent-like odor

Directions for use:
Brush, descale and degrease the part to be treated.
Shake the aerosol before use.
Spray at a distance of 10 to 15 cm from the support.
Apply at least two coats for optimal protection.
Dry to the touch: 2 to 5 minutes
Drying time between 2 coats: 30 minutes to 1 hour
Yield 1 can of 500mL covers approximately 5 to 8 m2 in 1 coat

Areas of use:
- Metal construction industries
- Packaging lines
- Taps, bolts, welding
- Metallurgy

Packaging:
Packaging unit (U.C): Aerosol 500mL
Tinplate case diameter: 65 mm/Height: 195mm
Nominal volume: 650mL / Net volume: 500mL
Sales unit: Box of 12 units
Palettization: 1080 units / 90 boxes

Legislation:
GENERAL PUBLIC AND PROFESSIONAL USE
Dangerous. Respect the precautions for use. Consult the safety data sheet (SDS), available on request.
Our technical data sheets have been produced based on our current knowledge; certain elements are subject to change. Non-contractual photo. 01/01/2026 Index 3,1

S.I.C.O.
MADE IN FRANCE

SIEGE SOCIAL / HEADQUARTER
577 rue du Pommarin B.P. 16 Voreppe
38341 Moirans CEDEX France
+33 (0)4 76 50 85 50 / accueil@sico.fr

SARL AU CAPITAL DE 4 700 000 EUROS
R.C. GRENOBLE 57 B 150
SIRET 697 320 539 00045 – APE 8292 Z
N°TVA CEE : FR 71 697 320 539