





RECOMMENDED FOR

- Manufacturing sites
- Maritime facilities
- Schools
- Commercial buildings
- Food-processing plants

PACKAGING

Packaging unit (PU): Aerosol can

Sales unit (SU): Box of 12 units

<u>Pallet size:</u> 1080 units – 90 boxes

Tin can diameter: 65 mm/Height: 195 mm

Nominal volume: 650 ml -Net volume 500 ml



- Oxidation protection
- Corrosion protection
- Can be used as primer
- Matte finish

APPLICATION

Protects metal, iron, steel and galvanized sheet metal against oxidation and corrosion.

For application on rails, guardrails, welding beads, galvanized metal parts, metal constructions, nuts and bolts, valves, welded joints.

For indoor and outdoor protection of iron, steel, galvanized sheet metal such as frames, structures, roofing, signage, etc.

Can be used as primer. Matte finish

Specifications:

- <u>Touch dry:</u> several minutes
- <u>Hardening</u>: 12 hours

INSTRUCTIONS

Before each use, the temperature of the aerosol can must be at least 15°C. Shake well until the ball can clearly be heard. Continue shaking for 1 min. Brush, descale and degrease the area to be treated, then spray from 10 to 15 cm away.

After each use, purge the aerosol can upside down until only gas comes out.

REGULATIONS

FOR PROFESSIONAL USE ONLY. Hazardous. Follow precautions for use. Refer to the safety data sheet (SDS), available upon request. Our data sheets are prepared with current knowledge and are subject to modifications. Photo non-binding. 01/01/2024 Index 1.0

