

DIELECTRIC CLEANER

Ref. A25403 - 400mL

QUICK
TECH

OFFICE
AUTOMATION



Suitable for regular maintenance of electronic components

- Very fast drying
- Leaves no greasy residue



APPLICATION

Cleaner for de-energized electrical contacts.

For maintenance of:

Read/write heads, magnetic tapes, magnetic media, telephones

Degreasing of finished devices and accessories

Cleaning of electronic components: relays, switches, contactors

Office equipment industry: part cleaning, etc.

Fields of application: Electricity, electronics, IT, precision mechanics, etc.

Electronics: Removal of photoresist ink residues and solder flux from printed circuit boards.

Specifications:

- Density: 0.71 +/- 0.02
- Odour: hydrocarbon

RECOMMENDED FOR

- Office buildings
- Multimedia retail outlets
- Printing facilities
- IT rooms (secondary schools, high schools, university libraries)
- Internet cafés
- Etc.

PACKAGING

Packaging unit (P.U.):
400 mL aerosol

Sales unit (S.U.):
Box of 12 units

Palletization:
1,440 units – 120 boxes

Tinplate can: Diameter 65 mm /
Height 157 mm

Nominal volume: 520 mL

Net volume: 400 mL

INSTRUCTION

Do not use on live equipment. Turn off all devices.

Shake well before use. Hold the aerosol upright, nozzle pointing upward.

Spray onto the parts to be cleaned, keeping the extension tube a few centimeters from the surface.

Allow to dry before powering the equipment back on.

Ensure good ventilation after use.

REGULATIONS

FOR INDIVIDUAL AND PROFESSIONAL USE.

Hazardous. Follow precautions for use. Refer to the safety data sheet (SDS), available upon request.

Our data sheets are prepared using current knowledge and are subject to modifications. Refer to the safety data sheet (SDS), available upon request. Non-binding image. 01/01/2024 Index 1.0

S.I.C.O.

577 Rue du Pommarin B.P. 16 – Voreppe - 38341 Moirans CEDEX France
Tel: +33 (0)4 76 50 85 50 / sico.commercial@sico.fr / www.sico.fr